

EPSON®

Projectors, Displays & Document Cameras

2023 Line Guide



Optional camera sold separately.

	Budget-Friendly Classroom Projectors			Basic Projectors for Small and Medium Rooms
Note: Highlighted boxes indicate step-ups between models within a series.				
Epson® Model	PowerLite® E20	PowerLite X49	PowerLite W49	PowerLite 1288
Product Code	V11H981020	V11H982020	V11H983020	V11H978120
Replacement Lamp Code	V13H010L97	V13H010L97	V13H010L97	V13H010L97
Previous Epson Model	PowerLite S39	PowerLite X39	PowerLite W39	PowerLite 1286
Limited Warranty	2-year	2-year	2-year	2-year
1- and 2-Year Extended Service Plans	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2
3-Year Extended Service Plan	EPPEXA3	EPPEXA3	EPPEXA3	EPPEXA3
Basics				
Color Brightness (Color Lumens)*	3,400	3,600	3,800	4,000
White Brightness (White Lumens)*	3,400	3,600	3,800	4,000
Native Resolution**	XGA	XGA	WXGA	1080p
Weight	5.9 lb	5.9 lb	5.9 lb	6.8 lb
Dimensions (Inches)†	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	12.1 x 11.5 x 4.1
Contrast Ratio (up to)	15,000:1	16,000:1	16,000:1	16,000:1
Throw Ratio	1.44 Wide, 1.95 Tele	1.48 Wide, 1.77 Tele	1.30 Wide, 1.56 Tele	1.32 Wide, 2.14 Tele
Zoom Lens (Ratio)	1.35x Digital	1.2x Optical	1.2x Optical	1.6x Optical
Light Source	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle up to (Normal/Medium/ECO [Hours])††	6,000/-/12,000	6,000/-/12,000	8,000/10,000/17,000	5,500/-/12,000
Power Consumption	345 W	345 W	345 W	345 W
Value-Added Features				
Built-In Speaker	5 W	5 W	5 W	16 W
Closed Captioning	YES	YES	YES	YES
A/V Mute	Slide Door	Slide Door	Slide Door	Slide Door
Split Screen*****	YES	YES	YES	YES
Edge Blending	-	-	-	-
Scheduling Function	-	-	-	-
Easy Connectivity and Setup				
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)***	-	YES	YES	YES
Epson Projector Content Manager Software****	-	-	-	-
Miracast®	-	-	-	YES
USB Plug 'n Play Image/Video	-	YES	YES	YES
PC-Free Presentations via USB Type-A	-	Images	Images	Photo, Motion JPEG
Quick Corner® Adjustments	YES	YES	YES	YES
Screen Fit	-	-	-	-
Keystone (Horizontal/Vertical)	Manual/Manual	Manual/Auto	Manual/Auto	Manual/Auto
Easy-Slide Horizontal Keystone Adjustment	YES	YES	YES	YES
Lens Shift (Vertical and Horizontal)	-	-	-	-
LAN Networking and Control				
Wired	-	RJ-45 (Content over IP)	RJ-45 (Content over IP)	-
Wireless*****	-	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n), QR Code Quick Connect
Compatible Control Systems	-	Crestron®, AMX®, Extron®, Control4®	Crestron, AMX, Extron, Control4	-
Connections				
HDMI®	HDMI x 1	HDMI x 1	HDMI x 2	HDMI x 2
Analog Connections	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 1, Composite x 1
Audio In	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA x 1
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	-
USB 2.0 Connectors	Type-B x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	-
DisplayPort/DVI-D	-	-	-	-
HDBaseT®	-	-	-	-
SDI	-	-	-	-
Monitor Out	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	-
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1	-
Recommended Accessory 1	Soft Carrying Case (ELPKS70)	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	ES3000 Screen
Recommended Accessory 1 SKU	V12H00K70	V12H005A02	V12H005A02	V12H002S3Y
Recommended Accessory 2	DC-13 Document Camera	DC-13 Document Camera	DC-13 Document Camera	Carrying Case
Recommended Accessory 2 SKU	V12H757020	V12H757020	V12H757020	V12H001K70

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. **WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600). ***For wireless functionality, including via the Epson iProjection app, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection app does not support all files and formats. See www.epson.com for details. ****Internet connection required for download. Data usage fees may apply. *****Wi-Fi CERTIFIED™; level of performance subject to the range of the router being used.

Advanced Networking Classroom Projectors – Standard Throw

				
PowerLite 118	PowerLite 119W	PowerLite U50	PowerLite 982W	PowerLite 992F
V11HA03020	V11H985020	V11H952020	V11H987020	V11H988020
V13H010L97	V13H010L97	V13H010L97	V13H010L97	V13H010L97
PowerLite 108	PowerLite 109W	PowerLite 975W	PowerLite 980W	PowerLite 990U
2-year	2-year	2-year	2-year	2-year
EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2
EPPEXA3	EPPEXA3	EPPEXA3	EPPEXA3	EPPEXA3
3,800	4,000	3,700	4,200	4,000
3,800	4,000	3,700	4,200	4,000
XGA	WXGA	WUXGA	WXGA	1080p
6.2 lb	6.2 lb	6.8 lb	6.8 lb	6.8 lb
11.8 x 10.2 x 3.6	11.8 x 10.2 x 3.6	14.3 x 9.8 x 3.7	12.2 x 11.5 x 4.1	12.2 x 11.5 x 4.1
16,000:1	16,000:1	16,000:1	16,000:1	16,000:1
1.48 Wide, 1.77 Tele	1.38 Wide, 1.56 Tele	1.38 Wide, 1.68 Tele	1.38 Wide, 2.24 Tele	1.32 Wide, 2.14 Tele
1.2x Optical	1.2x Optical	1.2x Optical	1.6x Optical	1.6x Optical
Lamp	Lamp	Lamp	Lamp	Lamp
8,000/10,000/17,000	8,000/10,000/17,000	10,000/-/17,000	6,500/10,000/17,000	6,500/10,000/17,000
345 W	345 W	298 W	345 W	345 W
16 W	16 W	5 W	16 W	16 W
YES	YES	YES	YES	YES
Slide Door	Slide Door	Slide Door	Slide Door	Slide Door
YES	YES	YES	YES	YES
–	–	–	–	–
–	–	YES	–	–
YES	YES	YES	YES	YES
–	–	–	–	–
–	–	–	–	YES
YES	YES	YES	YES	YES
Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs
YES	YES	YES	YES	YES
–	–	–	–	–
Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
YES	YES	–	YES	YES
–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n)
Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2
VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2	VGA x 2, Composite x 1	VGA x 2, Composite x 1
RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1
–	–	–	–	–
–	–	–	–	–
–	–	–	–	–
D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1	D-Sub (15-Pin) x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	Ceiling Mount (ELPMB60)	Wireless LAN Module (ELPAP11)	Universal Mount (ELPMBPJG)
V12H005A02	V12H005A02	V12H963010	V12H005A02	V12H808001
DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera
V12H758020	V12H758020	V12H758020	V12H758020	V12H758020

†Dimensions including feet and standard lens.







††Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. The lamp comes with a 90-day limited warranty.

Advanced Networking Classroom Laser Projectors – Short Throw		Advanced Networking Projectors – Ultra Short Throw	Advanced Networking Laser Projectors for Classrooms and Digital Signage – U			
						
PowerLite L210SF	PowerLite L210SW	PowerLite 685W	PowerLite 760W	PowerLite 770F	PowerLite 775F	PowerLite 800F
V11HA75020	V11HA76020	V11H744520	V11HA81020	V11HA79020	V11HA83120	V11H923520
–	–	V13H010L91	Laser	Laser	Laser	Laser
–	–	PowerLite 585W	–	–	–	PowerLite 700U
3-year ^d	3-year ^d	2-year	3-year ^d	3-year ^d	3-year ^d	3-year ^d
EPPEXPE1, EPPEXPE2	EPPEXPE1, EPPEXPE2	EPPEXPA1, EPPEXPA2	EPPEXPF1, EPPEXPF2	EPPEXPF1, EPPEXPF2	EPPEXPF1, EPPEXPF2	EPPEXPF1, EPPEXPF2
–	–	EPPEXPA3	–	–	–	–
4,000	4,000	3,500	4,100	4,100	4,100	5,000
4,000	4,000	3,500	4,100	4,100	4,100	5,000
1080p	WXGA	WXGA	WXGA	1080p	1080p	1080p
9.9 lb	9.9 lb	12.6 lb	12.5 lb	12.5 lb	12.5 lb	21.4 lb
12.8 x 3.6 x 13.3	12.8 x 3.6 x 13.3	14.5 x 15.8 x 7.4	14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25	18.1 x 17.7 x 9.0
2,500,000:1	2,500,000:1	14,000:1	2,500,000:1	Dynamic 2,500,000:1, Native 1,400:1	Dynamic 2,500,000:1, Native 1,400:1	Dynamic 2,500,000:1, Native 1,440:1
0.45 Wide, 0.61 Tele	0.48 Wide, 0.65 Tele	0.28 Wide, 0.37 Tele	0.28 Wide, 0.37 Tele	0.26 Wide, 0.36 Tele	0.26 Wide, 0.36 Tele	0.27 Wide, 0.37 Tele
1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital
Laser	Laser	Lamp	Laser	Laser	Laser	Laser
20,000 ^h /-/30,000	20,000 ^h /-/30,000	5,000 ^h /-/10,000	20,000 ^h /-/30,000	20,000 ^h /-/30,000	20,000 ^h /-/30,000	20,000 ^h /-/30,000
265 W	265 W	373 W	267 W	267 W	267 W	381 W
16 W	16 W	16 W	16 W	16 W	16 W	8 W x 2
YES	YES	YES	YES	YES	YES	YES
Digital	Digital	Digital	Digital	Digital	Digital	Digital
YES	YES	YES	YES	YES	YES	YES
–	–	–	–	YES	YES	YES
–	–	–	–	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
–	–	–	–	YES	YES	YES
YES	YES	–	YES	YES	YES	YES
YES	YES	–	YES	YES	YES	YES
YES	YES	–	YES	YES	YES	YES
–	–	–	–	–	–	–
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
–	–	–	–	–	–	–
–	–	–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Included (802.11 a/b/g/n/ac); 2.4/5 GHz	Included (802.11 a/b/g/n/ac); 2.4/5 GHz	Optional (802.11 b/g/n)	Included (802.11 a/b/g/n/ac); 5 GHz	Included (802.11 b/g/n), 2.4 GHz; (802.11 a/n/ac), 5 GHz	Included (802.11 b/g/n), 2.4 GHz; (802.11 a/n/ac), 5 GHz	Optional (802.11 b/g/n), 2.4 GHz; (802.11 a/n/ac), 5 GHz
Crestron, AMX, Extron, Art-Net, PJLink	Crestron, AMX, Extron, Art-Net, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, PJLink, Art-Net, Control4	Crestron, AMX, Extron, PJLink, Art-Net, Control4	Crestron, AMX, Extron, PJLink, Art-Net, Control4
HDMI x 2	HDMI x 2	HDMI x 3 (Includes MHL [®] x 1)	HDMI x 3	HDMI x 3	HDMI x 3	HDMI x 3
VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video
RCA (L & R) x 1, Mini Stereo x 2, Mic In	RCA (L & R) x 1, Mini Stereo x 2, Mic In	Mini Stereo x 3	Mini Stereo x 3, Mic In	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1, Type-A with 2 Amp power x 1	Type-B x 1, Type-A with 2 Amp power x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 2	Type-B x 1, Type-A with 2 AMP power x 1	Type-B x 1, Type-A with 2 AMP power x 1	Type-B x 1, Type-A x 2
–	–	–	–	–	–	–
–	–	–	–	–	–	YES
–	–	–	–	–	–	–
Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1, HDMI out
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Short Throw Wall Mount (ELPMB64)	Short Throw Wall Mount (ELPMB64)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)	Ultra Short Throw Wall Mount (ELPMB62)
V12HA39010	V12HA39010	V12HA06A05	V12HA06A05	V12HA06A05	V12HA06A05	V12HA06A05
PowerLite Pilot™ 3 Connection and Control Box (ELPCB03)	PowerLite Pilot 3 Connection and Control Box (ELPCB03)	PowerLite Pilot 3 Connection and Control Box (ELPCB03)	DC-21 Document Camera	DC-21 Document Camera	PowerLite Pilot 3 Connection and Control Box (ELPCB03)	Wireless LAN Module
V12H927020	V12H927020	V12H927020	V12H758020	V12H758020	V12H927020	V12H005A02








‡20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first. †5-year with product registration.

Ultra Short Throw	Ultra Mobile Projectors – 1700 Series, Extra Thin and Light			
				
PowerLite 805F	PowerLite 1780W	PowerLite 1781W	PowerLite 1785W	PowerLite 1795F
V11H923620	V11H795020	V11H794120	V11H793020	V11H796020
Laser	V13H010L94	V13H010L94	V13H010L94	V13H010L94
PowerLite 700U	PowerLite 1761W	PowerLite 1771W	PowerLite 1776W	–
3-year ^Δ	2-year	2-year	2-year	2-year
EPPEXP1, EPPEXP2	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2	EPPEXA1, EPPEXA2
–	EPPEXA3	EPPEXA3	EPPEXA3	EPPEXA3
5,000	3,000	3,200	3,200	3,200
5,000	3,000	3,200	3,200	3,200
1080p	WXGA	WXGA	WXGA	1080p
21.4 lb	4.0 lb	4.0 lb	4.0 lb	4.0 lb
18.1 x 17.7 x 9.0	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1
Dynamic 2,500,000:1, Native 1,440:1	10,000:1	10,000:1	10,000:1	10,000:1
0.27 Wide, 0.37 Tele	1.04 Wide, 1.26 Tele	1.04 Wide, 1.26 Tele	1.04 Wide, 1.26 Tele	1.02 Wide, 1.23 Tele
1.35x Digital	1.2x Optical	1.2x Optical	1.2x Optical	1.2x Optical
Laser	Lamp	Lamp	Lamp	Lamp
20,000 [†] /-/30,000	4,000 [†] /-/7,000	4,000 [†] /-/7,000	4,000 [†] /-/7,000	4,000 [†] /-/7,000
381 W	290 W	290 W	309 W	309 W
8 W x 2	1 W	1 W	1 W	1 W
YES	YES	YES	YES	YES
Digital	Slide Door	Slide Door	Slide Door	Slide Door
YES	YES	YES	YES	YES
YES	–	–	–	–
YES	–	–	–	–
YES	YES	YES	YES	YES
YES	–	–	–	–
YES	–	–	YES	YES
YES	YES	YES	YES	YES
YES	Video, Images	Video, Images	Video, Images, PDF	Video, Images, PDF
YES	YES	YES	YES	YES
–	–	–	YES	YES
Manual/Manual	Manual/Auto	Manual/Auto	Auto/Auto	Auto/Auto
–	–	–	–	–
–	–	–	–	–
RJ-45 (Content over IP)	–	–	–	–
Optional (802.11 b/g/n), 2.4 GHz; (802.11 a/n/ac), 5 GHz	Included (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)
Crestron, AMX, Extron, PJLink, Art-Net, Control4	–	–	–	–
HDMI x 3	HDMI x 1	HDMI x 1	HDMI x 1	HDMI x 1
VGA x 2, Composite Video	VGA x 1, Composite Video	VGA x 1, Composite Video	VGA x 1, Composite Video	VGA x 1, Composite Video
Mini Stereo x 3	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Mini Stereo x 1	–	–	–	–
Type-B x 1, Type-A x 2	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1
–	–	–	–	–
YES	–	–	–	–
–	–	–	–	–
Mini D-Sub (15-Pin) x 1, HDMI out	–	–	–	–
RS-232c x 1	–	–	–	–
Ultra Short Throw Wall Mount (ELPMB62)	ES3000 Screen	ES3000 Screen	ES3000 Screen	ES3000 Screen
V12HA06A05	V12H002S3Y	V12H002S3Y	V12H002S3Y	V12H002S3Y
Wireless LAN Module	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera
V12H005A02	V12H758020	V12H758020	V12H758020	V12H758020

††20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.
^Δ5-year with product registration.

	Meeting Room and Large Room Projectors – 2000 Series		PowerLite Long Throw Laser Projectors			
Note: Highlighted boxes indicate step-ups between models within a series.						
Epson Model	PowerLite 2250U	PowerLite L210W	PowerLite L260F	PowerLite L265F	PowerLite L520W	PowerLite L520U
Product Code	V11H871020	V11HA70020	V11HA69020	V11HA72120	V11HA31020	V11HA30020
Replacement Lamp Code	V13H010L95	Laser	Laser	Laser	Laser	Laser
Previous Epson Model	PowerLite 1980WU	PowerLite L200W	PowerLite L250F	PowerLite L255F	PowerLite L500W	PowerLite L400U
Limited Warranty	2-year	3-year	3-year	3-year	3-year	3-year
1- and 2-Year Extended Service Plans	EPPEXPB1, EPPEXPB2	EPPEXPE1, EPPEXPE2	EPPEXPE1, EPPEXPE2	EPPEXPE1, EPPEXPE2	EPPEXPE1, EPPEXPE2	EPPEXPE1, EPPEXPE2
3-Year Extended Service Plan	EPPEXPB3	–	–	–	–	–
Basics						
Color Brightness (Color Lumens)*	5,000	4,500	4,600	4,600	5,200	5,200
White Brightness (White Lumens)*	5,000	4,500	4,600	4,600	5,200	5,200
Native Resolution**	WUXGA	WXGA	1080p	1080p	WXGA	WUXGA
Weight	10.2 lb	9.5 lb	9.5 lb	9.5 lb	16.1 lb	17.0 lb
Dimensions (Inches)†	14.9 x 11.5 x 5.0	19.1 x 14.4 x 6.9	19.1 x 14.4 x 6.9	19.1 x 14.4 x 6.9	17.32 x 11.97 x 4.80	17.32 x 11.97 x 4.80
Contrast Ratio (up to)	15,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Throw Ratio	1.38 Wide, 2.28 Tele	1.41 Wide, 2.26 Tele	1.32 Wide, 2.12 Tele	1.32 Wide, 2.12 Tele	1.38 Wide, 2.24 Tele	1.35 Wide, 2.20 Tele
Zoom Lens (Ratio)	1.0x – 1.6x Optical	1.0x – 1.6x Optical	1.0x – 1.6x Optical	1.0x – 1.6x Optical	1.00x – 1.6x Optical	1.00x – 1.6x Optical
Light Source	Lamp	Laser	Laser	Laser	Laser	Laser
Light Source Life Cycle up to (Normal/Medium/ECO [Hours])††	5,000/10,000	20,000*	20,000*	20,000*	20,000*	20,000*
Power Consumption	429 W	272 W	272 W	272 W	301 W	301 W
Value-Added Features						
Built-In Speaker	16 W	16 W	16 W	16 W	10 W	10 W
Closed Captioning	YES	YES	YES	YES	YES	YES
A/V Mute	YES	YES	YES	YES	YES	YES
Split Screen*****	YES	YES	YES	YES	YES	YES
Edge Blending	–	–	YES	YES	–	YES
Camera	–	–	–	–	–	–
Scheduling Function	YES	YES	YES	YES	YES	YES
Easy Connectivity and Setup						
Epson iProjection Suite (Moderator, Multi-PC, Device Management)***	YES	YES	YES	YES	YES	YES
Epson Creative Content Projection App for Signage	–	–	YES	YES	YES	YES
Miracast	–	YES	YES	YES	–	Optional
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES	YES
PC-Free Presentations via USB Type-A	YES	YES	YES	YES	YES	YES
Quick Corner Adjustments	YES	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–	–
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
Easy-Slide Horizontal Keystone Adjustment	YES	YES	YES	YES	–	–
Lens Shift (Vertical and Horizontal)	–	–	–	–	–	–
LAN Networking and Control						
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless****	Optional (802.11 b/g/n)	Included (802.11 b/g/n/a/ac); 2.4 GHz and 5 GHz	Included (802.11 b/g/n/a/ac); 2.4 GHz and 5 GHz	Included (802.11 b/g/n/a/ac); 2.4 GHz and 5 GHz	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Compatible Control Systems	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, PJLink, Control4	Crestron, AMX, Extron, PJLink, Art-Net, Control4	Crestron, AMX, Extron, PJLink, Art-Net, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4
Connections						
HDMI	HDMI x 2 (Includes MHL x 1)	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2
Analog Connections	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2	VGA x 2
Audio In	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	RCA (L & R) x 1, Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
USB 2.0 Connectors	Type-B x 1, Type-A x 1	Type-A with 5V/2A power supply, Type-B	Type-A with 5V/2A power supply, Type-B	Type-A with 5V/2A power supply, Type-B	Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1
DisplayPort/DVI-D	–	–	–	–	–	–
HDBaseT	–	–	–	–	YES	YES
SDI	–	–	–	–	–	–
Monitor Out	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1	Mini D-Sub (15-Pin) x 1
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Recommended Accessory 1	Universal Projector Mount (ELPMBPJG)	Ceiling Mount (ELPMB60W)	Ceiling Mount (ELPMB60W)	Ceiling Mount (ELPMB60B)	Projector Ceiling Mount (ELPMBPJG/ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG/ELPMBPRH)
Recommended Accessory 1 SKU	V12H808001	V12H963210	V12H963210	V12H963110	V12H808001/V12H809001	V12H808001/V12H809001
Recommended Accessory 2	Wireless LAN Module (ELPAP11)	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)
Recommended Accessory 2 SKU	V12H731P02	V12H758020	V12H758020	V12H758020	V12H005A02	V12H005A02


*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. **WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600). ***For wireless functionality, including via the Epson iProjection app, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection app does not support all files and formats. See www.epson.com for details. ****Wi-Fi CERTIFIED; level of performance subject to the range of the router being used. *****Split Screen feature requires remote control. Consult your user manual for input combinations.

						
PowerLite L770U	PowerLite L775U	EB-PU1006W	EB-PU1007W	EB-PU1007B	EB-PU1008W	EB-PU1008B
V11HA96020	V11HA96120	V11HA35920	V11HA34920	V11HA34820	V11HA33920	V11HA33820
Laser	Laser	Laser	Laser	Laser	Laser	Laser
-	-	Pro L1060UNL	Pro L1070UNL	Pro L1075UNL	Pro L1490UNL	Pro L1495UNL
3-year	3-year	3-year	3-year	3-year	3-year	3-year
EPPEXE1, EPPEXE2	EPPEXE1, EPPEXE2	EPPEXC1, EPPEXC2	EPPEXC1, EPPEXC2	EPPEXC1, EPPEXC2	EPPEXC1, EPPEXC2	EPPEXC1, EPPEXC2
-	-	-	-	-	-	-
7,000	7,000	6,000	7,000	7,000	8,500	8,500
7,000	7,000	6,000	7,000	7,000	8,500	8,500
WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**
19.1 lb	19.1 lb	34.2 lb	36.2 lb	36.2 lb	36.2 lb	36.2 lb
17.32 x 11.97 x 4.80	17.32 x 11.97 x 4.80	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5
2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
1.35 Wide, 2.20 Tele	1.35 Wide, 2.20 Tele	See Page 10 for Lens Options				
1.00x – 1.6x Optical	1.00x – 1.6x Optical	See Page 10 for Lens Options				
Laser	Laser	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor
20,000	20,000	20,000†	20,000†	20,000†	20,000†	20,000†
382 W	382 W	384 W	448 W	448 W	559 W	559 W
10 W	10 W	-	-	-	-	-
-	-	-	-	-	-	-
YES	YES	Digital	Digital	Digital	Digital	Digital
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
YES	YES	-	-	-	-	-
-	-	-	-	-	-	-
YES	YES	YES	YES	YES	YES	YES
YES	YES	-	-	-	-	-
YES	YES	YES	YES	YES	YES	YES
-	-	-	-	-	-	-
Manual	Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
-	-	-	-	-	-	-
YES	YES	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net
HDMI x 2, HDMI Out x 1	HDMI x 2, HDMI Out x 1	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)
-	-	VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1
-	-	-	-	-	-	-
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1, Type-A x 1	Type-B x 1, Type-A x 1	Type-B x 1 (For Service, Clone), Type-A x 1 (For Wireless, FW Update, Clone)				
-	-	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1
YES	YES	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)
-	-	-	-	-	-	-
-	-	-	-	-	-	-
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Projector Ceiling Mount (ELPMBPJG/ELPMBPRH)	Projector Ceiling Mount (ELPMBPJG/ELPMBPRH)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)
V12H808001/V12H809001	V12H808001/V12H809001	V12HA54010	V12HA54010	V12HA54010	V12HA54010	V12HA54010
Wireless LAN Module (ELPAP11)	Wireless LAN Module (ELPAP11)	PixAlign™ Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)
V12H005A02	V12H005A02	V12HA46010	V12HA46010	V12HA46010	V12HA46010	V12HA46010

‡20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.

‡‡4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen.

Large Venue Installation – Pro Series Laser Projectors with Optional Lenses

						
EB-PU2010W	EB-PU2010B	EB-PU2113W	EB-PU2213B	EB-PU2116W	EB-PU2216B	EB-PU2120W
V11HA52920	V11HA52820	V11HA65920	V11HA68820	V11HA64920	V11HA67820	V11HA63920
Laser	Laser	Laser	Laser	Laser	Laser	Laser
–	–	Pro L1500UH	Pro L1505UH	Pro L1750U	Pro L1755U	Pro L20002U
3-year	3-year	3-year	3-year	3-year	3-year	3-year
EPPEXPC1, EPPEXPC2	EPPEXPC1, EPPEXPC2	EPPPRJPU3 3-Yr. NBD ^Δ (WUE) [‡] Upgrade / EPPPRJPUE5 5-Yr. NBD ^Δ (WUE) [‡] Upgrade & Extension				EPPPRJPU3 3-Yr. NBD ^Δ (WUE) [‡] Upgrade / EPPPRJPUE5 5-Yr. NBD ^Δ (WUE) [‡] Upgrade & Extension
–	–	–	–	–	–	–
10,000	10,000	13,000	13,000	16,000	16,000	20,000
10,000	10,000	13,000	13,000	16,000	16,000	20,000
WUXGA with 4K Enhancement ^{‡‡}	WUXGA with 4K Enhancement ^{‡‡}	WUXGA with 4K Enhancement ^{‡‡}	HD WUXGA with 4K Enhancement ^{‡‡}	HD WUXGA with 4K Enhancement ^{‡‡}	HD WUXGA with 4K Enhancement ^{‡‡}	HD WUXGA with 4K Enhancement ^{‡‡}
37.5 lb	37.5 lb	52.4 lb	52.2 lb	53.5 lb	53.5 lb	53.7 lb
21.5 x 17.2 x 6.5	21.5 x 17.2 x 6.5	23.07 x 19.37 x 7.3	23.07 x 19.37 x 7.3	23.07 x 19.37 x 7.3	23.07 x 19.37 x 7.3	23.07 x 19.37 x 7.3
2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
See Page 10 for Lens Options						
Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor
20,000 [†]	20,000 [†]	20,000 [†]	20,000 [†]	20,000 [†]	20,000 [†]	20,000 [†]
559 W	559 W	886 W	886 W	1,118 W	1,118 W	1,301 W
–	–	–	–	–	–	–
–	–	–	–	–	–	–
Digital	Digital	Digital	Mechanical Shutter	Digital	Mechanical Shutter	Digital
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)	Optional (ELPEC01)
YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–
–	–	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–
–	–	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
–	–	–	–	–	–	–
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
–	–	–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net
–	–	–	–	–	–	–
HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)
VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1	VGA x 1
–	–	–	–	–	–	–
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-B x 1 (For Service, Clone), Type-A x 3 (For Wireless, FW Update, Clone, Camera)						
DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1
HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)
3G-SDI In/Out	3G-SDI In/Out	–	3G-SDI In/Out	–	3G-SDI In/Out	–
–	–	–	–	–	–	–
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)	Ceiling Mount (ELPMB67)
V12HA54010	V12HA54010	V12HA54010	V12HA54010	V12HA54010	V12HA54010	V12HA54010
PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)	PixAlign Camera (ELPEC01)
V12HA46010	V12HA46010	V12HA46010	V12HA46010	V12HA46010	V12HA46010	V12HA46010

^{‡‡}20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.
^ΔNBD = Next-Business-Day; WUE = Whole Unit Exchange.

Note: Highlighted boxes indicate step-ups between models within a series.	Interactive Projectors – BrightLink Series				
	BrightLink 760Wi	BrightLink 770Fi	BrightLink GoBoard 780Fi	BrightLink 1480Fi	BrightLink 1485Fi
Interactive Features					
Pens	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support	2 Pens Included, Dual-User Support
Pen Technology	IR, 850 nm				
Finger Touch	Optional, up to 6 Fingers	Optional, up to 6 Fingers	Optional, up to 6 Fingers	Optional, up to 6 Fingers	Included, up to 6 Fingers
Interactive Pen Functions	Mouse Function (Left/Right Click), Digital Pen, LED Battery Status Indicator				
PC-Free Whiteboard Sharing	YES	YES	YES	YES	YES
DuoLink® Extended Whiteboard ^o	–	–	–	–	YES, with Edge Blending
Calibration	Automatic or Manual				
Interactive Image Size	16:10 up to 100"	16:9 up to 100", 16:6 up to 110"	16:9 up to 100"	16:9 up to 100"	16:9 up to 100", 16:6 up to 120"
Interactive Connectivity	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN
PC-Free Annotation	YES	YES	YES	YES	YES
PC-Free Digital Whiteboard	Up to 20 Pages	Up to 20 Pages	Up to 20 Pages	Up to 20 Pages	Up to 20 Pages
Wall-Mounted Control Panel	–	–	–	–	YES
PC-Free Save, Email, Print	YES	YES	YES	YES	YES
Android™ OS	–	–	YES, with Chromium browser	–	–
Gesture Support	YES, computers require Windows® 7/8/10/11 or Mac® OS 10.x				
Included Software ^{oo}	Easy Interactive Tools for PC/Mac, Built-In Annotation Toolbar				

^oRequires Easy Interactive Driver. Certain functionality is only available through Epson Interactive Tools (EIT) software. For a list of supported operating systems, visit www.epson.com
^{oo}Not available on BrightLink GoBoard 780Fi.

Lenses Compatible with Pro Series Projectors up to 8,500 Lumens										
Epson Model	Ultra Short Throw Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Middle Lens #1	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Lens Model	ELPLX01S	ELPLU03S	ELPLU04	ELPLW05	ELPLW06	ELPLM08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
Product Code	V12H004X0A	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004M08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	1.0x	1.0x – 1.2x	1.0x – 1.2x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.6x	1.0x – 1.6x	1.0x – 1.5x	1.0x – 1.5x	1.0x – 1.4x
Throw Ratio (16:10)	0.35	0.65 – 0.78	0.87 – 1.05	1.04 – 1.46	1.62 – 2.22	1.42 – 2.28	2.16 – 3.48	3.32 – 5.06	4.85 – 7.38	7.21 – 10.11
White Version	V12H004Y0A	–	–	–	–	–	–	–	–	–

Lenses Compatible with Pro Series Projectors 10,000 to 20,000 Lumens										
Epson Model	Ultra Short Throw Lens	Short Lens #1	Short Lens #2	Wide Lens #1*	Wide Lens #2	Wide Lens #3	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Lens Model	ELPLX02S	ELPLU03S	ELPLU04	ELPLW05*	ELPLW06	ELPLW08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
Product Code	V12H004X0B	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004W08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	1.0x	1.0x – 1.2x	1.0x – 1.2x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.4x	1.0x – 1.6x	1.0x – 1.5x	1.0x – 1.5x	1.0x – 1.4x
Throw Ratio (16:10)	0.35	0.48 – 0.57	0.64 – 0.77	0.77 – 1.07	1.19 – 1.62	0.86 – 1.21	1.57 – 2.56	2.42 – 3.71	3.54 – 5.41	5.27 – 7.41
White Version	V12H004Y0B	–	–	–	–	–	–	–	–	–

*ELPLW05 lens has limited compatibility with 16,000 lm and higher projectors.




An Essential Teaching Tool for the Modern Classroom

Share books, 3D objects and detailed demonstrations or experiments with your entire class using Epson's easy-to-use document cameras. Record lessons for viewing at a later time and give your students a more interactive learning experience.

Comprehensive Warranty with Convenient Road Service

Epson projector customers receive first-class service with Epson's standard 2-year limited warranty^{oo}, including Road Service and a dedicated toll-free support line. Epson laser projectors receive a standard 3-year limited warranty^{oo}.

^{oo}Lamps have a 90-day limited warranty. Select Pro L projectors do not offer "Road Service".

Document Cameras			
			
Epson Model	DC-07	DC-13	DC-21
Product Code	V12H759020	V12H757020	V12H758020
Limited Warranty	2-year		
Extended Service Plan	EPPELPDC10		
Zoom	8x Digital	16x Digital	12x Optical, 10x Digital
Pixel Count	2MP	2MP	2MP
Output Resolution (Max.)	1080p	1080p	1080p
Frame Rate	15 fps	30 fps	30 fps
Connectivity (Output)	USB	USB, VGA, HDMI	USB, VGA, HDMI
Capture Area	10.7" x 14.3"	11.7" x 20.7"	11.7" x 20.7"
A/V Recording	YES	YES	YES
Built-In Microphone	YES	YES	YES
Microscope Adapter	–	YES	YES
SD Card Slot ^{oo}	–	YES	YES
Software Included	YES	YES	YES

^{oo}SD card sold separately.

Note: Highlighted boxes indicate step-ups between models within a series.

Epson® Model

Product Code

Replacement Lamp Code

Previous Epson Model

Limited Warranty

1- and 2-Year Extended Service Plans

3-Year Extended Service Plan

Basics

Color Brightness (Color Lumens)*

White Brightness (White Lumens)*

Native Resolution**

Weight

Dimensions (Inches)†

Contrast Ratio (up to)

Throw Ratio

Zoom Lens (Ratio)

Light Source

Light Source Life Cycle up to
(Normal/Medium/ECO [Hours])††

Power Consumption

Value-Added Features

Built-In Speaker

Closed Captioning

A/V Mute

Split Screen*****

Edge Blending

Scheduling Function

Easy Connectivity and Setup

Epson iProjection™ Suite
(Moderator, Multi-PC, Device Management)***

Epson Projector Content Manager Software****

Miracast®

USB Plug 'n Play Image/Video

PC-Free Presentations via USB Type-A

Quick Corner® Adjustments

Screen Fit

Keystone (Horizontal/Vertical)

Easy-Slide Horizontal Keystone Adjustment

Lens Shift (Vertical and Horizontal)

LAN Networking and Control

Wired

Wireless*****

Compatible Control Systems

Connections

HDMI®

Analog Connections

Audio In

Variable Audio Out

USB 2.0 Connectors

DisplayPort/DVI-D

HDBaseT®

SDI

Monitor Out

Serial Control

Recommended Accessory 1

Recommended Accessory 1 SKU

Recommended Accessory 2

Recommended Accessory 2 SKU



LightScene® Accent Lighting Laser Projectors

LightScene laser projectors elevate ordinary spaces into stunning visual environments, unleashing dynamic, experiential content for digital art, spatial design, signage and wayfinding applications.

LightScene Projectors		
Epson Model	EV-110	EV-115
Product Code	V11HA22020	V11HA22120
Product Color	White	Black
Limited Warranty	3 Years or 20,000 Hours, Whichever Comes First	
Color Brightness (Color Lumens)*	2,200	
White Brightness (White Lumens)*	2,200	
Native Resolution	WXGA (1280 x 800)	
Contrast Ratio (Dynamic)	Up to 2,500,000:1	
Light Source Life	Up to 20,000 hours**	
Left/Right, Up/Down Movement	180 Degrees	
Ball-Joint Axis Rotation	360 Degrees	
Zoom (Powered)	1.58x	
Edge Blending Capable	YES	
HDMI/SD Card Slot ⁰⁰	1 x HDMI, 1 x SD Card Slot	
Variable Audio Out	1 x Stereo, Mini Out	
GPI Motion Sensor Compatible	YES	
Bluetooth® Audio	YES	
Epson Creative Content Projection App for Signage***	YES	
Epson Projector Content Manager Software***	YES	

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

**No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period.

***Internet connection required for download. Data usage fees may apply.

Epson Laser Projection Technology

As a world leader in digital 3LCD projection solutions, Epson continues to drive the future of projection technology with its full suite of laser projectors and displays. Featuring lamp-free, long-life, laser light engines, Epson laser solutions achieve new levels of performance and reliability¹.






Why Choose Laser?

Breakthrough laser technology — long-life laser light engine provides up to 20,000 hours of light source life¹

Outstanding color performance and contrast — get exceptional, true-to-life color reproduction and deep, dark blacks for stunning visuals you can count on for an array of applications

Instant Off®/On — displays and projectors reach maximum brightness and turn off almost instantly, without having to warm up or cool down

Reliable operation — ideal for applications requiring extended projection

Explore Epson's Suite of Laser Projectors and Displays				
				
Laser Large Venue Projectors	Interactive Laser Displays	Portable Laser Projectors	Ultra Short Throw Laser Displays	Lighting Laser Displays
High-lumen laser projectors designed for exceptional performance in large venues	Full HD, ultra short throw interactive laser displays for collaborative meetings and learning	High-performance laser projectors offering a variety of brightness, connectivity and resolutions	Bold, rich, Full HD laser displays for virtually any application, including those in small spaces, without any shadows	Project dynamic, experiential content for digital art, commercial signage and décor applications

Epson PreferredSM Plus Extended Service Plans*

We've got you covered.

Epson Preferred Plus Extended Service Plans offer you peace of mind with a variety of flexible plan options to best fit your needs and budget, helping you maximize uptime and protect your investment.

For more information, go to www.epson.com/esp



Extended Service Plans*

1-Year Next-Business-Day Whole Unit Exchange (Years 3-5), PowerLite Series Below Model 2000 ¹	EPPEXPA1
2-Year Next-Business-Day Whole Unit Exchange (Years 3-5), PowerLite Series Below Model 2000 ¹	EPPEXPA2
3-Year Next-Business-Day Whole Unit Exchange (Years 3-5), PowerLite Series Below Model 2000 ¹	EPPEXPA3
1-Year Next-Business-Day Whole Unit Exchange (Years 3-5), PowerLite Series Models 2000 and Above ¹	EPPEXPB1
2-Year Next-Business-Day Whole Unit Exchange (Years 3-5), PowerLite Series Models 2000 and Above ¹	EPPEXPB2
3-Year Next-Business-Day Whole Unit Exchange (Years 3-5), PowerLite Series Models 2000 and Above ¹	EPPEXPB3
1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5), Pro L ² , EB-PU 1000 Series and EB-PU2010	EPPEXPC1
2-Year Next-Business-Day Whole Unit Exchange (Years 4-5), Pro L ² , EB-PU 1000 Series and EB-PU2010	EPPEXPC2
1-Year Return for Repair Extension (Year 4 or 5), Pro L20000UNL, Pro L30000UNL	EPPEXPD1
2-Year Return for Repair Extension (Years 4-5), Pro L20000UNL, Pro L30000UNL	EPPEXPD2
1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5), PowerLight L Series, W70 Series and LightScene Series	EPPEXPE1
2-Year Next-Business-Day Whole Unit Exchange (Years 4-5), PowerLight L Series, W70 Series and LightScene Series	EPPEXPE2
1-Year Next-Business-Day Whole Unit Exchange (Year 4 or 5), BrightLink, PowerLite 700 and 800 Series	EPPEXPF1
2-Year Next-Business-Day Whole Unit Exchange (Years 4-5), BrightLink, PowerLite 700 and 800 Series	EPPEXPF2
2-Year Next-Business-Day Whole Unit Exchange, Document Camera	EPPELDC10
3-Year Shipping Upgrade to Next-Business-Day (Years 1-3), EB-PU Series Models 2010 and Above	EPPPRJPU3
5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5), EB-PU2113W, EB-PU2116W, EB-PU2213B, EB-PU2216B	EPPPRJPU5
5-Year Next-Business-Day Upgrade (Years 1-3) and Extension (Years 4-5), EB-PU2120W, EB-PU2220B	EPPPRJPU20E5

¹ Lamp-based models only. ² Pro L12000, Pro L20000 and Pro L30000 not eligible for Next-Business-Day replacement. *Check individual Extended Service Plans for Terms and Conditions. Coverage varies by plan.

Epson Business Solutions

Epson is a leading provider of innovative technology solutions that help businesses succeed. We partner with you to best meet your specific needs, focusing on:

- Improved productivity
- World-class customer service and support
- Cost-effective, high-quality solutions
- A commitment to the environment

Discover how Epson can help you work toward the future at www.epson.com/forbusiness

EPSON[®]

Epson America, Inc.
3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited
185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.com/projectors

¹ No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. Large Venue Series: 20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first. The EB-PU Series of projectors have a standard limited warranty of 3 years. Interactive, Digital Signage and Accent Lighting Projectors: 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. Interactive and Digital Signage Projectors come with a 3-year limited warranty; Accent Lighting Projectors have a limited warranty of 3 years or 20,000 hours, whichever comes first. Corporate Series: 20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.

Specifications and terms are subject to change without notice. EPSON, Instant Off, LightScene, PowerLite and Quick Corner are registered trademarks, the EPSON logo is a registered logomark and Epson iProjection is a trademark of Seiko Epson Corporation. BrightLink is a registered trademark, BrightLink GoBoard, Pilot and PixAlign are trademarks and Epson Preferred is a service mark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google LLC. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and other countries. Miracast[®] is a registered trademark of Wi-Fi Alliance[®]. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2023 Epson America, Inc. CPD-63281 2/23